

DARH ■ DARHD

Core Area (ft ²)	Size (in.)			Core Velocity (FPM)	300	400	500	600	700	800	1000	1200	1400
				Velocity Pressure (in. w.g.)	0.006	0.010	0.016	0.022	0.031	0.040	0.062	0.090	0.122
				Neg. Static Pressure (in. w.g.)	0.036	0.064	0.101	0.145	0.197	0.258	0.403	0.580	0.790
0.18	8x4	7x5	6x6	Airflow (CFM)	54	72	90	108	126	144	180	216	252
0.20	10x4			Airflow (CFM)	60	80	100	120	140	160	200	240	280
0.26	12x4	10x5	8x6	Airflow (CFM)	78	104	130	156	182	208	260	312	364
0.29	14x4			Airflow (CFM)	87	116	145	174	203	232	290	348	406
0.33	16x4	12x5	10x6	Airflow (CFM)	99	132	165	198	231	264	330	396	462
0.38	18x4 14x5	12x6	8x8	Airflow (CFM)	114	152	190	228	266	304	380	456	532
0.45	20x4 16x5	14x6	10x8	Airflow (CFM)	135	180	225	270	315	360	450	540	630
0.52	24x4	18x5	16x6	Airflow (CFM)	156	208	260	312	364	416	520	624	728
0.58	28x4 20x5	18x6 12x8	10x10	Airflow (CFM)	174	232	290	348	406	464	580	696	812
0.68	30x4 24x5	20x6 14x8	12x10	Airflow (CFM)	204	272	340	408	476	544	680	816	952
0.79	36x4 28x5	22x6 16x8	14x10	Airflow (CFM)	237	316	395	474	553	632	790	948	1106
0.87	40x4 30x5	26x6 18x8	12x12	Airflow (CFM)	261	348	435	522	609	696	870	1044	1218
1.05	48x4 36x5	30x6 22x8	18x10 14x12	Airflow (CFM)	315	420	525	630	735	840	1050	1260	1470
1.18	40x5 34x6	24x8 20x10	16x12 14x14	Airflow (CFM)	354	472	590	708	826	944	1180	1416	1652
1.35	46x5 38x6	28x8 22x10	18x12 16x14	Airflow (CFM)	405	540	675	810	945	1080	1350	1620	1890
1.60	44x6 26x10	22x12 18x14	16x16	Airflow (CFM)	480	640	800	960	1120	1280	1600	1920	2240
1.77	50x6 36x8	28x10 24x12	20x14 18x16	Airflow (CFM)	531	708	885	1062	1239	1416	1770	2124	2478
2.06	58x6 42x8	28x12 24x14	20x16 18x18	Airflow (CFM)	618	824	1030	1236	1442	1648	2060	2472	2884
2.37	48x8 38x10	32x12 26x14	24x16 20x18	Airflow (CFM)	711	948	1185	1422	1659	1896	2370	2844	3318
2.73	44x10 36x12	30x14 26x16	24x18 22x20	Airflow (CFM)	819	1092	1365	1638	1911	2184	2730	3276	3822
3.04	48x10 40x12	34x14 30x16	26x18 24x20	Airflow (CFM)	912	1216	1520	1824	2128	2432	3040	3648	4256



Scan for more product information.

Performance notes at the end of the section.

mail@dayus.com ■ www.dayus.com ■ (519) 737-1199



DARH ■ DARHD

Core Area (ft ²)	Size (in.)			Core Velocity (FPM)	300	400	500	600	700	800	1000	1200	1400
				Velocity Pressure (in. w.g.)	0.006	0.010	0.016	0.022	0.031	0.040	0.062	0.090	0.122
				Neg. Static Pressure (in. w.g.)	0.036	0.064	0.101	0.145	0.197	0.258	0.403	0.580	0.790
3.71	58 x 10 48 x 12	36 x 16 32 x 18	28 x 20 24 x 24	Airflow (CFM)	1113	1484	1855	2226	2597	2968	3710	4452	5194
4.28	68 x 10 56 x 12	42 x 16 36 x 18	32 x 20 28 x 24	Airflow (CFM)	1284	1712	2140	2568	2996	3424	4280	5136	5992
4.64	72 x 10 60 x 12	44 x 16 40 x 18	36 x 20 30 x 24	Airflow (CFM)	1392	1856	2320	2784	3248	3712	4640	5568	6496
5.50	84 x 10 72 x 12	60 x 14 54 x 16	48 x 18 42 x 20	Airflow (CFM)	1650	2200	2750	3300	3850	4400	5500	6600	7700
6.33	84 x 12 70 x 14	54 x 18 48 x 20	40 x 24 32 x 30	Airflow (CFM)	1899	2532	3165	3798	4431	5064	6330	7596	8862
6.64	72 x 14 42 x 24	36 x 28 46 x 22	32 x 32	Airflow (CFM)	1992	2656	3320	3984	4648	5312	6640	7968	9296
7.08	36 x 30	38 x 28		Airflow (CFM)	2124	2832	3540	4248	4956	5664	7080	8496	9912
7.60	48 x 24 34 x 34	36 x 32 38 x 30		Airflow (CFM)	2280	3040	3800	4560	5320	6080	7600	9120	10640
8.09	36 x 34 38 x 32	40 x 30 48 x 26		Airflow (CFM)	2427	3236	4045	4854	5663	6472	8090	9708	11326
8.71	36 x 36 38 x 34	44 x 30 48 x 28		Airflow (CFM)	2613	3484	4355	5226	6097	6968	8710	10452	12194

Performance Notes:

1. Tested in accordance with ASHRAE Standard 70-2023 "Method of Testing for Rating the Performance of Air Outlets and Inlets."
2. Air flow is in CFM.
3. All pressures are in w.g.
4. Throw values are given for terminal velocities of 150, 100 and 50 FPM under isothermal conditions.
5. The performance tables are based on **DARH** grilles without opposed blade dampers.



Scan for more product information.

